

TABLE OF SPECIFICATIONS

681A

Type:	Moving Coil Dynamic
Pickup Pattern:	Omnidirectional
Frequency Response:	50 to 18,000 cycles
Output Impedance:	150/250 Ω or 20,000 Ω
Output Level (Ref.: 10 dynes/ cm ²):	-55 dbm
Hum (Ref.: 10 ⁻³ Gauss):	-120 db
Dimensions (not including cable and plug):	1-1/8" top diameter, 7-3/8" long
Weight (not including cable and plug):	10 ozs (including cable)*
Finish:	Two-tone baked enamel; black and dark green, or brushed chrome

Mounting:

*"Snap-on" swivel adapter is supplied for attachment to any microphone stand having standard 5/8-27 thread. Microphone comes complete with 15 feet of 2-conductor shielded cable (100% shield) and a 3-pin Cannon XLR-3-11C Plug for connection to the microphone.
*The 681A Microphone comes with the cable connected to the microphone which eliminates the necessity of the microphone plug.

Accessories:

See "Microphone Accessories" sheet for desk or floor stands, on-off switches, adapters, and other microphone accessories.

Should your microphone, through accidental damage, become inoperative it may be replaced by your Altec Distributor under an exchange plan or may be returned, transportation charges prepaid, for exchange; Service Manager; Altec Lansing, 1515 South Manchester Ave., Anaheim, Calif.

Specifications and components subject to change without notice. Overall performance will be maintained or improved.



A Division of RCA Victor Company, Inc.

1515 S. Manchester Ave., Anaheim, Calif.
New York

40514-1

Litho in USA

Price \$0.

CP-117-